

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1-7 in the underlying PCT Application No. PCT/DE03/02212 and adds new claims 8-16. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. No new matter has been added. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE03/02212 includes an International Search Report, dated November 4, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is respectfully submitted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

[Signature] (reg no 36098)

Dated: 14 Feb 2005

By: *[Signature]*

Richard L. Mayer
Reg. No. 22, 490

One Broadway
New York, NY 10004
(212) 425-7200
(212) 425-5288

CUSTOMER NO. 26646

[10191/3627]

METHOD FOR OPERATING AN INTERNAL COMBUSTION ENGINE

~~Related Art~~ FIELD OF THE INVENTION

The present invention relates to a control device and a method for operating an internal combustion engine in which a valve needle of a fuel injector is adjusted from a closing position via an intermediate position to an opening position and back, with the aid of a piezoelectric actuator to which a trigger signal is applied.

~~Furthermore, the present invention relates to a control device for an internal combustion engine in which a valve needle of a fuel injector is adjusted from a closing position via an intermediate position to an opening position and back, with the aid of a piezoelectric actuator to which a trigger signal is applied.~~

BACKGROUND INFORMATION

~~Such an~~ Conventional operating method as well as a method and control device ~~devices~~ for such a method ~~are already known from the related art. Disadvantages arise in the known system especially from a~~ may be disadvantageous signal form of the trigger signal in that, which, on the one hand, ~~leads~~ they may lead to an increased contamination risk of the fuel injector and, on the other hand, ~~prevents~~ they may prevent a controlled closing of the fuel injector.

The increased contamination risk is due to the fact that the fuel injector is in a state of a comparatively low lift of the injection needle, and thus reduced opening of the fuel injector, for a relatively long period of time. The danger that particles get jammed between the valve orifice and the valve needle and clog the valve orifice is especially great in this state.

A greater slope steepness of the trigger signal leads to greater velocity of the valve needle in the transition from the opening to the closing position and vice versa, but, due to the high velocity of the valve needle, so-called needle bouncers occur when the valve needle hits the valve seat, which cause the fuel injector to open in an uncontrolled manner after reaching the closing position. Furthermore, overswingers of the valve needle may occur.

SUMMARY

~~Consequently, it~~ It is the objective an object of the present invention to improve an operating method and a control device of the type mentioned in the introduction to the extent that the

contamination risk of the fuel injector is reduced and the valve needle is adjusted, or is able to be adjusted, into the opening and closing position in a controlled manner.

~~This~~In accordance with an example embodiment of the present invention, this object is~~may be achieved in a method as recited in the preamble of Claim 1 in that~~if, for example, the trigger
5 signal has a greater slope steepness in the transition of the valve needle from the closing position to the intermediate position than in the transition of the valve needle from the intermediate position to the opening position.

10 The relatively high slope steepness of the trigger signal for the piezoelectric actuator during the transition of the valve needle from the closing position to the intermediate position effects a rapid readjustment of the valve needle out of the closing position into the intermediate position, so that the period during which the fuel injector has a low needle lift is relatively brief, thereby reducing the likelihood of valve contamination or clogging due to jammed particles.

15 Accordingly, the relatively low slope steepness of the trigger signal for the piezoelectric actuator leads to a controlled reaching of the opening position by the valve needle during the transition of the valve needle from the intermediate position to the opening position, in which the valve needle, in particular, does not bounce so that no uncontrolled adjustment of the valve
20 needle takes place in the opening position.

According to ~~an~~one advantageous embodiment of the present invention, the trigger signal has a greater slope steepness during the transition of the valve needle from the opening position to the intermediate position than during the transition of the valve needle from the intermediate
25 position to the closing position. As a result, analogously to the opening procedure of the fuel injector, the same advantages are derived regarding the duration of the opening period of the fuel injector at low needle lift, or regarding the controlled attainment of the closing position by the valve needle.

30 In particular, the valve needle does not bounce off the valve seat due to the relatively low slope steepness of the trigger signal during the transition of the valve needle from the intermediate position to the closing position, so that no uncontrolled opening of the fuel injector occurs after the valve needle has reached the closing position.

35 ~~Another~~In accordance with another advantageous embodiment of the present invention ~~is characterized by the fact that~~, during the transition of the valve needle from the opening position to the closing position, the trigger signal is symmetrical to the trigger signal during the transition of the valve needle from the closing position to the opening position.

Due to the symmetry, the triggering of the piezoelectric actuator is considerably simplified since the signal form of the trigger signal must be stored only for a transition of the valve needle, i.e., either for the transition of the valve needle from the closing position to the opening position or vice versa. The respective other trigger signal may be generated by subtraction of the stored signal values of the trigger signal from a maximum signal value for the trigger signal or the like, for instance. This is possible both in an analog and a digital triggering of the piezoelectric actuator.

As an additional ~~achievement of the objective~~embodiment of the present invention, a computer program for a control device of an internal combustion engine is provided in which a valve needle of a fuel injector is adjusted from a closing position via an intermediate position to an opening position and back by means of a piezoelectric actuator to which a trigger signal is applied, the computer program being suited for implementing the example method according to the present invention.

Exceedingly advantageous is another variant of the present invention in which the computer program is stored on an electric storage medium, in particular a flash memory or a read-only memory.

Yet another ~~achievement of the objective of the present invention is realized by~~advantage may be achieved by providing a control device for an internal combustion engine ~~according to one of the Claims 6 or 7.~~

Further features, uses and advantages of the present invention come to light from the following description of exemplary embodiments of the present invention, which are shown in the figures of the drawing. In this context, all of the described or represented features, alone or in any combination, constitute the subject matter of the present invention, regardless of their ~~combination in the claims or their antecedents, as well as regardless of their~~ formulation and representation in the specification and the drawings, respectively.

~~The figures show:~~

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 ~~the~~ shows a time characteristic of a trigger signal according to the present invention;

Figure 2 ~~the~~ shows a time characteristic of another trigger signal according to the present invention.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

Trigger signal SA shown in Figure 1 is utilized in an internal combustion engine (not shown) to trigger a piezoelectric actuator, which adjusts a valve needle of an injection valve of the internal combustion engine from a closing position via an intermediate position to an opening position and back.

In the diagram of Figure 1, t denotes the time axis and A a value of trigger signal SA standardized to the maximum value of trigger signal SA. Trigger signal SA is an analog signal.

For the further elucidation of the method according to the present invention, a plurality of regions SZ, Z0, OZ, ZS of trigger signal SA are marked in the diagram of Figure 1, which are described in the following.

At the beginning of an injection, the piezoelectric actuator (not shown) is triggered by a ~~likewise not shown~~ control device of the internal combustion engine by the portion of trigger signal SA lying in region SZ in which trigger signal SA has a relatively great slope steepness. This ~~ensures~~may ensure that the valve needle of the fuel injector is rapidly adjusted from the closing position, which corresponds to a zero value of trigger signal SA, into the intermediate position, so that states of low needle lift and thus a clogging risk caused by jammed particles are avoided.

Subsequently, the piezoelectric actuator is triggered during the transition from the intermediate position to the opening position, which corresponds to a value one of trigger signal SA, by a trigger signal SA having relatively low slope steepness, thereby defining region Z0 of trigger signal SA. The low slope steepness of trigger signal SA in region Z0 has the effect that the valve needle is not too fast when it reaches the opening position and will not move out of the attained opening position again in an uncontrolled manner due to bouncing, or will open in an uncontrolled manner due to overswinging. Subsequently, trigger signal SA is maintained at its maximum value of one for a certain period of time.

~~As can be gathered from~~shown in Figure 1, trigger signal SA initially traverses region OZ during the closing procedure, the valve needle of the fuel injector being adjusted from the opening position to the intermediate position. Here, the slope steepness of trigger signal SA is relatively high again so as to reduce the already mentioned danger of valve contamination.

At the end of the injection phase, which corresponds to region ZS of trigger signal SA, trigger signal SA once again has a relatively low slope steepness in order to prevent valve needle from hitting the valve seat of the fuel injector too rapidly, and thus to avoid bouncing of the valve needle, which leads to uncontrolled openings of the fuel injector.

In this way it is possible to reduce the risk of valve contamination and simultaneously achieve a controlled opening and closing of the fuel injector.

It is also possible to implement the triggering of the piezoelectric actuator by a digital signal.

5 To this end, Figure 2 shows a corresponding diagram in which the time characteristic of digital trigger signal SD is indicated. The functioning method is identical to the triggering of the piezoelectric actuator by the analog trigger signal SA.

10 Since the time for adjusting the valve needle from the opening position to the closing position is determined nearly exclusively by the kinematics of a system made up of the valve needle and a spring mechanically acting upon the valve needle with an initial stress, it is advantageous to consider the mechanical parameters of the system valve needle/spring in the selection of the signal form of trigger signal SA or SD so as to achieve an optimal division of the valve travel having high/low slope steepness.

15 Particularly advantageous is also a symmetry between the signal form of trigger signal SA, SD, which is used in the adjustment of the valve needle from the closing position to the opening position, and the signal form of trigger signal SA, SD, which is utilized in the adjustment of the valve needle from the opening position to the closing position. In this case, it is possible to
20 store only one signal form, for example in a memory of the control device, and to generate the respective other signal form from the stored signal form.

The afore-described method ~~is~~may be realized as computer program, which is able to run on the control device and is stored in its memory.

25 In general, the example method according to the present invention may be used in metering systems having components that are driven by piezoelectric actuators.

Summary ABSTRACT

~~The present invention relates to a~~ method for operating an internal combustion engine in which a valve needle of a fuel injector is adjusted from a closing position via an intermediate position to an opening position and back again. The adjustment is carried out with the aid of a piezoelectric actuator to which a trigger signal (~~SA~~) is applied. To reduce the contamination danger of the fuel injector and to keep wear of the valve needle low, the trigger signal (~~SA~~) for triggering the piezoelectric actuator has a greater slope steepness during the transition of the valve needle from the closing position to the intermediate position than during the transition of the valve needle from the intermediate position to the opening position.

(~~Figure 1~~)